GGPv 6570

Liebherr Reach-In freezers







Exterior Dim W/D/H Packaged Dim		
Packaged Dim W/D/H Energy Efficiency Class Energy Consumption per year Noise level Refrigerant Refrigerant Rolled Rolled Rolled Refrigerant Rolled	Climate Class	5
Energy Efficiency Class Energy Consumption per year Noise level Refrigerant R 290 Ambient Temp +10C to 40C Connection rating 4.0 A Voltage 220-240V Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Temperature Display Warning Signal Optical and Acoustical Smart Monitoring Enabled Refrigerator Compartment Gross Volume/Net Volume Frequency Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Handle Handle Handle Interior Self-Closing Doors Pes Connecting Cable length Type of lock Fitted Weight without Packaging 114/140 kgs		
Energy Consumption per year Noise level 60db Refrigerant R 290 Ambient Temp +10C to 40C Connection rating 4.0 A Voltage 220-240V Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Electronic Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs		
Noise level60dbRefrigerantR 290Ambient Temp+10C to 40CConnection rating4.0 AVoltage220-240VFrequency50HzCONTROLS AND FUNCTIONSControl UnitElectronic Control UnitTemperature DisplayExternal digitalWarning SignalOptical and AcousticalSmart Monitoring EnabledYesRefrigerator Compartment597L/465LTemp Range-10C to -26CCooling SystemDynamicDefrostingAutomaticNo of Shelves4DESIGN AND MATERIALStainless steelColour and MaterialStainless steelHandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs		
Refrigerant R 290 Ambient Temp +10C to 40C Connection rating 4.0 A Voltage 220-240V Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Electronic Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs		1874kwh/a
Ambient Temp +10C to 40C Connection rating 4.0 A Voltage 220-240V Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Electronic Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs		60db
Connection rating 4.0 A Voltage 220-240V Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Electronic Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs		R 290
Voltage220-240VFrequency50HzCONTROLS AND FUNCTIONSElectronic Control UnitControl UnitElectronic Control UnitTemperature DisplayExternal digitalWarning SignalOptical and AcousticalSmart Monitoring EnabledYesRefrigerator Compartment597L/465LGross Volume/Net Volume597L/465LTemp Range-10C to -26CCooling SystemDynamicDefrostingAutomaticNo of Shelves4DESIGN AND MATERIALStainless steelColour and MaterialStainless steelHandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Ambient Temp	+10C to 40C
Frequency 50Hz CONTROLS AND FUNCTIONS Control Unit Electronic Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Connection rating	
CONTROLS AND FUNCTIONS Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Voltage	220-240V
Control Unit Temperature Display External digital Warning Signal Optical and Acoustical Smart Monitoring Enabled Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Handle Interior Shelf Plastic-coated grids Self-Closing Doors Poor Hinges Right reversible Castors Yes Connecting Cable length Type of lock Fitted Weight without Packaging	Frequency	50Hz
Temperature Display Warning Signal Optical and Acoustical Smart Monitoring Enabled Refrigerator Compartment Gross Volume/Net Volume Temp Range	CONTROLS AND FUNCTIONS	
Warning Signal Optical and Acoustical Smart Monitoring Enabled Yes Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Control Unit	Electronic Control Unit
Smart Monitoring Enabled Refrigerator Compartment Gross Volume/Net Volume 597L/465L Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length Type of lock Fitted Weight without Packaging	Temperature Display	External digital
Refrigerator Compartment Gross Volume/Net Volume Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Handle Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length Type of lock Fitted Weight without Packaging	Warning Signal	Optical and Acoustical
Gross Volume/Net Volume Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length Type of lock Fitted Weight without Packaging	Smart Monitoring Enabled	Yes
Temp Range -10C to -26C Cooling System Dynamic Defrosting Automatic No of Shelves 4 DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Refrigerator Compartment	
Cooling SystemDynamicDefrostingAutomaticNo of Shelves4DESIGN AND MATERIALColour and MaterialStainless steelHandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Gross Volume/Net Volume	597L/465L
DefrostingAutomaticNo of Shelves4DESIGN AND MATERIALColour and MaterialStainless steelHandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Temp Range	-10C to -26C
No of Shelves DESIGN AND MATERIAL Colour and Material Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length Type of lock Weight without Packaging	Cooling System	Dynamic
DESIGN AND MATERIAL Colour and Material Stainless steel Handle Moulded Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Defrosting	Automatic
Colour and MaterialStainless steelHandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	No of Shelves	4
HandleMouldedInteriorChrome-Nickel steel AISI 304ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	DESIGN AND MATERIAL	
Interior Chrome-Nickel steel AISI 304 Shelf Plastic-coated grids Self-Closing Doors Yes Door Hinges Right reversible Castors Yes Connecting Cable length 380 cm Type of lock Fitted Weight without Packaging 114/140 kgs	Colour and Material	Stainless steel
ShelfPlastic-coated gridsSelf-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Handle	Moulded
Self-Closing DoorsYesDoor HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Interior	Chrome-Nickel steel AISI 304
Door HingesRight reversibleCastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Shelf	Plastic-coated grids
CastorsYesConnecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Self-Closing Doors	Yes
Connecting Cable length380 cmType of lockFittedWeight without Packaging114/140 kgs	Door Hinges	Right reversible
Type of lockFittedWeight without Packaging114/140 kgs	Castors	Yes
Weight without Packaging 114/140 kgs	Connecting Cable length	380 cm
	Type of lock	Fitted
/Weight with Packaging	Weight without Packaging	114/140 kgs
	/Weight with Packaging	

